

CertwoodUSA: StorSystem™ Mobile Series

CE2302: Swift II Cart **Wide Line**, Double Column, 12 Module Cart (shown)



Tray Color Options:

Standard Colors: Primary Red, Primary Blue, Primary Green, Primary Yellow, Light Gray, Crystal Clear, Tinted Blue, Tinted Pink, Neon Green, Neon Orange.

(See Tote Tray Data Sheet for additional color options)

Metal Color Options:

White, Dark Gray, Light Gray, Platinum Silver

Tray Size Options:

Wide Line: single 3" and double 6" Depth
(W18 ½x L 16 ¾")

Swift II Cart 12 Module

Dimensions:

W 41 5/8 x H 29 3/8 x D 18"

Materials

The StorSystem "Mobile Series" metal cart frames are constructed from 16 gauge, 1" (25.4mm) square welded steel tubing with an epoxy powder coated finish. The top panel is constructed from 18 gauge formed steel, epoxy powder coated sheets securely anchored to the metal frames with machine screw fasteners. All mobile series metal carts have four, 3-inch heavy-duty rubber tire casters permitting ease of movement throughout environments.

The "shatterproof" tote tray structural Runners are molded from Acrylonitrile Butadiene Styrene (ABS) Plastic. These runners are secured to the steel frames with 1/4" tap screws. All cart solutions incorporate the patented Glide & Tilt Tote Tray Runner System. This innovative system is specifically designed to allow the accompanying ABS tote trays to stop in an angled open position without falling out of the unit, making for easy access and viewing.

Additional Specifications:

- *Top panels shall be constructed from 18 gauge formed steel; baked-on epoxy coated sheets securely fastened to the steel frames with hex head machine screw fasteners. "Optional" side and rear panels shall be constructed from 18 gauge formed steel, baked-on epoxy coated sheets securely fastened to the steel frames with hex head machine screw fasteners.*
- *Product coatings are specifically designed to resist wear, abrasion, corrosion and chemicals.*
- *Glide & Tilt® structural runners specifically designed for steel construction shall be manufactured with a vertical alignment rail to the inside of the runner.*
- *Mobile series metal cart frames shall be provided with (4) 3-inch heavy-duty swivel casters with, stainless steel bumper and sealed internal ball bearings to provide ease of movement. Casters shall be provided with friction fitted coated steel frame inserts.*
- *Depths of all units shall be 18" "out to out." This dimension incorporates an additional ½" projection for widest projection of the caster bumper for design purposes. The actual physical dimension of the upper frame assembly is 17".*
- *Mobile series carts shall be offered with six (6) "Slim Line" size options in two heights: 29 3/8" high units shall be provided in 6, 12 and 18 tray module options, 41 3/8" high units shall be provided in 9, 18 and 27 tote tray module options.*
- *Mobile series carts shall be offered with (4) "Wide Line" size options in two heights: 29 3/8" high units shall be provided in 6 and 12 tote tray module options, 41 3/8" high units shall be provided in 9 and 18 tote tray module options.*